Handle Via
TALENT. KEYHOLE

Approved for Release 7002/19/20/ TALENT. KEYHOLE

Approved for Release 7002/19/20/ TALENT. KEYHOLE

Approved for Release 7002/19/20/ TALENT. KEYHOLE

Control System Only

## NRO & USAF REVIEWS COMPLETED

COMIREX MAPPING, CHARTING AND GEODESY WORKING GROUP

Minutes of Meeting Held in Room 5B2830 Pentagon 1330 - 1600, 19 February 1968

1 Des

		PRESIDING	
25X1A			
	·		
		NOW TAXES DESCRIPTION	
.5.// .		NSULTANTS PRESENT	
25X1A			

Purpose of Meeting

1. The purpose of the meeting was announced as a briefing meeting to acquaint members with new activities or particular applications involving special data, to review progress in current collection programs in meeting MC&G requirements, and to indicate progress of the NRO toward meeting the worldwide positioning requirement.

Copy 26 of \_\_copies

25X1

Handle Via

Approved For Release 2962/16 E FIA-RDP79B01709A0005000 look file blue

rul

Handle Via
TALENT-KEYHOLE Approved Release 2010 POSTCRIA-RDP79B01709A000500010047-6

Control System Only

	Progress of Current Collection Programs
25X1A	2. from AMS briefed on progress with the following highlights:
	a. Regarding KH-4 panoramic coverage, Mission 1102 provided 90% cloud-free coverage of approximately 2 million square miles gross and 300,000 square miles of new (net) coverage toward MC&G requirements; similarly, Mission 1045, completed 7 February, yielded coverage 90% cloud-free for 2,500,000 square miles gross and 200,000 square miles new (net) coverage. As of 15 February 1968, the net coverage of KH-4 panoramic photography 90% cloud-free totals 16 million square miles toward the present total requirement area of 24.1 million square miles, leaving a remainder of approximately 8 million square miles.
	b. With regard to coverage of 3-inch frame photography (primarily KH-4 coverage), there was presently on hand photography covering 11,420,000 square miles toward meeting the generally worldwide requirement for 3-inch frame photography.
25X1D	
25X1D	
	It was noted that the requirement index for the KH-4 3-inch frame camera, including regions grouped for coverage by fiscal year, had not been presented previously. However, the need for this coverage generally worldwide, because of its improvement over the $1\frac{1}{2}$ -inch frame camera for both mapping and geodetic applications, had previously been discussed and stated in documents reviewed in the Working Group.
	Use of Special Data by NAVOCEANO
25X1A	of NAVOCEANO presented a briefing for the information of the group including the following:
	a. Items incorporating TKH and SI data as follows:
	(1) Hydrographic Chart of Novaya Zemlya, which used data from the AMS 1:250,000 photo maps made from TKH data.
	Common of comics

Handle Via Approved Release 20/12/10/54 CREARDP79B01209A000500010047-6 Release 20/12/10/54 CREARDP79B01209A000500010047-6

(2) 1.50 000 Hydrographic Chart of Walakasa Kana San L. I
(2) 1:50,000 Hydrographic Chart of Velekaya Kema, for which NAVOCEANO had set up models from satellite photography using the M-2 plotter to draw 50-meter topography.
b. Several products produced from KH-4 photography, including the 1:50,000 Hydrographic Chart of the Yalu River delta using KH-4 in the M-2 plotter, a 1:75,000 chart along the east coast of China which was based on an ACIC 1:250,000 MUM and a large-scale product at 1:12,500 also along the China east coast.
c. A total of approximately 55 charts have been produced by the Hydrographic Office utilizing TKH data at the scales of 1:12,500 to 1:250,000. In addition, a number of combat charts have been produced for which compilation covering the land area was obtained from AMS.
Plans for Use of TKH Data by US Geological Survey
4. of the Topographic Division of the US Geological Survey from the Department of the Interior, presented plans for developing a capability to utilize TKH data and described the USGS production plans with highlights as follows:
a. The USGS is working toward a 1 July opening date for a secure MC&G facility at Reston, Virginia, with 23,000 square feet of working space. The building is being adapted for M-4 plotters with respect to ceiling height and has features that will permit isolation of vibration and proper air handling. The USGS had received extensive assistance from the CIA with respect to security aspects of the new facility.
b. It is intended that 50 personnel will be ready to occupy the new facilities as of 1 July. Presently, the Department of the Interior has 100 billets total and 50 of these are set aside for the new operational facility at Reston. Personnel are being taken from present GS roles, and they are now looking for 35 new personnel for assignment to this facility. Key people to work in this facility have already been oriented or trained at AMS and ACIC. Present plans call for about 80 operational people in the new facility in the second year and in 5 years, 115 to 120 personnel.
c. All equipment needed for the Reston facility is either on hand or being purchased. The USGS does not plan to buy a Gamma rectifier, but has made arrangements with DIA and Army to have rectification work done at AMS.
Copy_of_copies

25X1A

25X1A

MCGWG-M-29

Handle Via
TALENT-KEYHOLE
Control System Only

Approved Release 2002716/16/RETA-RDP79B04209A000500010047-6

25X1A		
÷		
1 25X1A	indicated that discussion with had resolved that there would be a COMIREX briefing on the USGS use of special data, and a memo would be forwarded for USIB review covering this use of special data.	(1 <i>F</i>
25X1A	Special Positioning Applications of KH-4 Data by USAF  5. of USAF, described a 1970 project and 3 current projects involving special positioning applications of the KH-4 data with highlights as follows:	
	a. As a 1970 project in support of an Air Force tactical non-nuclear strike capability having a CEP of 200 feet, planning was underway to use new	
	Copy of copies	X1

25X1A

25X1

Handle Via
TALENT-KEYHOLE
Control System Only

techniques in a cooperative effort between field and stateside capability. The F-111s planned for this capability are presently expected to have radar sensing equipment which will require accurate horizontal position and accurate relationship of features. Concept-wise, it is envisioned that geographic data base, probably an ortho-photo presentation with spot elevations having the geometric fidelity of Class A 1:50,000 scale maps would serve the purpose. This would be produced in the ZI and made available to the theater. Theater RECCE would then spot the target which could be transferred to the geographic data base for the strike operation. It was thought that this concept could provide for servicing strike capability with both position and a data base in a 15-30 day time period. When the geographic data base is available in the theater for the local area in concern, it would be used immediately.

b. As a current project identified	d as positions
have been located by ACIC for targets in the	he North Viet Nam region, in order
to enable the effective use of MSQ-78 or 83	1 radar for guidance. It was neces-
sary for ACIC to produce a photogrammetric	extension base from the several
KH-4 flights over the area extending to the	e well-controlled areas of South
Viet Nam and over the target areas in North	h Viet Nam which were not located
correctly with respect to the radar site.	
identified precisely on RECCE photos to AC	IC. These had been transferred to
KH-4 position base and accurate coordinates	s wired back to Viet Nam.
indicated that this process had redu	9
around 635 feet to an evaluated accuracy of	
completed and the STRIKE Forces were using	this data.
	directly comparable to
described above had been undertaken as	
cal areas in North Korea. Only a limited	
This project had originated with PACAF and	
grammetric position base established for No	
time ACIC should be in a position to provide	• • • • • • • • • • • • • • • • • • •
in 1 day or 50 targets in 3 or 4 days. AC	
cooperation from AMS in providing control	
had expressed appreciation to Army, ACSI for	
this geographic area, it was known that ma	
curately located with respect to South Korto produce the position base to be prepared	
and other areas that may be found.	d for weak areas hear the border
and other areas that may be round.	
d. Project will und	ertake to complete target area cover-
age of North Viet Nam as started by	described above. This was
planned in the next 30-60 days.	
-	Conv. of contac
	Copy of copies

25X1A 25X1A

25X1A 25X1A 25X1A

25X1A 25X1A

Handle Via

Approved Release 20020103107 RCGWG-M-29 Handle Via TALENT-KEYHOLE Control System Only 25X1A indicated that the data base that had been prepared for Viet Nam and for Korea could be expected to meet positioning requirements in the next several years. He further mentioned that facsimile transmission from the ZI to the theater could provide improved service. He had been requested to present a briefing of this nature to the COMIREX Committee, and this was planned in the next 60-75 days. NRO Progress Toward Meeting Worldwide Positioning Requirement referred to a memo of October 1967 from 6. I 25X1A 25X1A the Director, NRO Staff, asking that NRO provide various alternative proposals to meet the worldwide positioning requirement. Responding to requests, of NRO re-25X1A 25X1A ported on the progress of his office toward meeting the USIB worldwide positioning requirement of 450 feet horizontal and 300 feet vertical, 90 % assurance. It was explained that the NRO was studying several approaches, some of which pertain to modifying existing systems on hand, and some pertaining to new systems in development. His office was compiling cost data on various modifications to existing systems, but mentioned that accomplishment of any changes during FY 69 would present problems because of the extremely tight budget. In essence, most of the existing systems have already been purchased, and any changes to these existing systems would have to come from current programs. His office was presently scheduled to brief concerning var- concerning var- ious proposals in the near future. Following this action, alternatives would be indicated to 25X1A 25X1A raised a question as to whether the positioning requirement of 450 feet horizontal and 300 feet vertical, 90% assurance, was impacted by the change in Air Force plans regarding the use of the Mark 17 re-entry vehicle. mentioned that both the Mark 11A and 12 required com-25X1A parable accuracies to the Mark 17, but recognized it would be desirable to update the requirements statement in this regard. 25X1A tioned that consideration was being given in DoD as to whether there may be a valid long-range requirement for reducing the position requirement to 210 feet horizontal and 115 feet vertical, 90% assurance. These figures have been determined to be feasible geodetic and geophysical objectives. He mentioned that an effort was being made to arrive at a statement that would express the probability of such a change in the worldwide positioning requirement. Other Business raised a question as to what action was being taken with 25X1A respect to reviewing the substantive information that had been distributed Copy copies

25X1

Handle Via Approved Release 20091916 Rel

i	or th	ne info	ormation of Work <u>ing Group me</u> mbers for the purpose of defining	
1	utur	e MC&G	requirements. noted that the discussion of the	
Ţ	revi	ous Wor	rking Group meeting had concluded that he, as Chairman of the Hotion	,
1	CGWG	, would	d d <u>iscuss with the detail he felt was needed in a</u>	
(	COMIRI	EX раре	er. indicated that his discussion with	
(	ited	change	es that his office would like to see in format of the information	
ŧ	o be	preser	nted, po <u>ssibly including graphics, and</u> that he would discuss the	
r	natter	r furth	her with	
_				
(	hair	nan		
(	COMIRI	EX MC&G	G Working Group	
I	ISTR:	IBUTION	<b>N:</b>	
(	Сору	1,2	DIA TCO	
		3,4	Army TCO	
		5,6	Navy TCO	
٠		7,8	Air Force TCO	
		9,10	CIA <u>Member</u>	
	ĵ	11,12	NRO	
		13	TSO CIA	
		14	State TCO	
		15	NSA TCO	
	]	16,17	NPIC	
		18	CIA COMIREX Member	
	]	19,20	CR SUBCOM	
		21_25	Ch/MCGWG	

26

Ch/COMIREX

Copy \_\_ of \_\_ copies 25X1